Digital LCR Meter

Category: Test & Measurement · Model reference: MZM-9017



SPECIFICATIONS

DESCRIPTION
MZM-9017-Digital LCR Meter features an innovative automatic selection technology. It automatically measures L, C and R with Q, D and q by just turning on the meter. The test frequency is selectable up to 100KHz. It also provides high accuracy read out with four or five terminal Kelvin measurements.

FEATURES

- Sampling rate: 5 times/sec
- Overload Indication: "OL" or "-OL"
- Auto Power Off: 10 minutes
- Low battery power indication
- Dust and water proof
- Five selectable test frequency: 100 / 120 / 1K / 10K / 100K Hz
- Operating Temp: 0~50ºC, <=80%R.H.
- Storage Temp: -20~60ºC
- Temp. coefficient: 0.15 (Spec. Acc)/ºC, <18ºC or >28ºC
- Safety Comply with IEC61000 EMC standard
- Power Requirement: AA size 1.5V X 4 batteries (NEDA15A or IEC LR6) Battery Life: 30 hours (Alkaline battery)

Send Enquiry **Your Name**
Your Email
Tele Phone





MZFIRSTMOTION SDN BHD · Reg No. 1137962-V · No 53, Lorong 1/SS3, Bandar Tasek Mutiara, 14120 Simpang Ampat, Pulau PinangT: +604-505 7422 · E: sales@mzfirstmotion.com · https://www.mzfirstmotion.com